

Combination wall mounting socket outlet - Belgian/French standard



| Product description | |
|---------------------------|--------------------------------------|
| BALS-Prd.-Nr | 1018 |
| EAN | 4024941010184 |
| Product category | Combined wall mounting socket outlet |
| Current | 32A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 - 240/415V~ |

| Product description | |
|------------------------|---|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Housing bottom grey RAL 7035, Housing top grey RAL 7035, Collar grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 6,0 qmm |
| Cable entry | 1xM25 top, 2xM25 bottom |
| Height | 157mm |
| Width | 83mm |
| Depth | 134mm |
| Dimension of enclosure | 126x83 mm (HxW) |
| Material of enclosure | plastic |
| Contacts | the contacts are brass |

| Additional technical information | |
|----------------------------------|--|
| | The cable entry is one at top open and two at bottom closed, With integrated Schuko-type socket outlet 16A 230V AC Belgian/French standard |
| | 4 cut out fixing holes in the lower part of housing |
| | with fusible link 6,3 A, with fuse base 5x20 mm DIN 41671, type 1862, With 3x6mm ² terminals with wiring |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.534 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941010184 |
| Length | 134 mm |
| Width | 83 mm |
| Height | 157 mm |
| Weight | 0.535 kg |
| Volume | 1,746.154 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941828291 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 5.566 kg |
| Volume | 17,062.5 ccm |



| | 16A | | 32A | |
|---|-----|-----|-----|-----|
| | 4p | 5p | 4p | 5p |
| a | 154 | 155 | 156 | 157 |
| b | 127 | 130 | 130 | 136 |

1 MB 17