

## Wall mounting socket outlet - straight - housing dimensions 102x102 mm




Product description	
BALS-Prd.-Nr	110557
EAN	4024941938549
Product category	Wall mounting socket outlet QUICK-CONNECT
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	4 h
Voltage	57/100 - 75/130V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	yellow RAL 1012
Colour of appliance	Hinged lid yellow RAL 1012, Enclosure grey RAL 7035
Connection design	screwless spring terminals with KONTEX-contact
Maximum conductor size	10,0 qmm
Cable entry	3 sides 2x M20/25, 1 side 1x M20/25, to break out
Height	106mm
Width	102mm
Depth	131mm
Dimension of enclosure	102x102 mm (HxW)
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass

Additional technical information	
	All cable entries are to break out

Logistics data	
Weight/pcs	0.435 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941938549
Length	131 mm
Width	102 mm
Height	106 mm
Weight	0.436 kg
Volume	1,416.372 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941826990
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.576 kg
Volume	17,062.5 ccm



1 MB 120

Ampere Polzahl	16 3	16 4	16 5	32 3	32 4	32 5
a	102,0	102,0	102,0	102,0	102,0	102,0
b	102,0	102,0	102,0	102,0	102,0	102,0
c	88,0	88,0	88,0	88,0	88,0	88,0
d	88,0	88,0	88,0	88,0	88,0	88,0
e	68,0	68,0	68,0	68,0	68,0	68,0
f	119,0	121,0	122,0	130,0	130,0	131,0
g	4,0	4,0	4,0	4,0	4,0	4,0
h ø	4,5	4,5	4,5	4,5	4,5	4,5
i	2xM20/25	2xM20/25	2xM20/25	2xM20/25	2xM20/25	2xM20/25
k	M20/25	M20/25	M20/25	M20/25	M20/25	M20/25
Leiter mm <sup>2</sup> min	1,5	1,5	1,5	2,5	2,5	2,5
Leiter mm <sup>2</sup> max	4	4	4	10	10	10