

wall mounting socket outlet, chemically resistant - housing dimensions 225x118



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 11999 |
| EAN | 4024941119993 |
| Product category | TE wall mounting socket outlet Quick-Connect |
| Current | 32A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 6 h |
| Voltage | 380 - 415V~ |

| Product description | |
|------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Housing bottom lightbeige, Housing top lightbeige, Housing screws lightbeige |
| Connection design | screwless spring terminals with Kontex-Kontakt |
| Maximum conductor size | 10,0 qmm |
| Cable entry | top entry M25/M25 bottom entry M25 |
| Height | 251mm |
| Width | 118mm |
| Depth | 135mm |
| Dimension of enclosure | 225x118 mm (HxW) |
| Material of enclosure | Polycarbonate+Polyester light - beige |
| Contacts | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | The cable entry is one at top open, one at top is closed, and two at bottom are closed |

| Logistics data | |
|----------------|----------------|
| Weight/pcs | 0.0 kg / Piece |
| Packaging | Carton |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941119993 |
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 0.125 kg |
| Volume | 5,737.5 ccm |



| Ampere | 16 | 32 | 32 | 32 | | | |
|----------------------------|---------|---------|---------|---------|--|--|--|
| Polzahl | 5 | 3 | 4 | 5 | | | |
| a | 118,0 | 118,0 | 118,0 | 118,0 | | | |
| b | 225,0 | 225,0 | 225,0 | 225,0 | | | |
| c | 101,0 | 101,0 | 101,0 | 101,0 | | | |
| d | 208,0 | 208,0 | 208,0 | 208,0 | | | |
| e | 130,0 | 125,0 | 125,0 | 141,0 | | | |
| f | 242,0 | 250,0 | 250,0 | 250,0 | | | |
| g ø | 6,5 | 6,5 | 6,5 | 6,5 | | | |
| h | 8,0 | 8,0 | 8,0 | 8,0 | | | |
| i | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | | | |
| k | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | | | |
| Leiter mm ² min | 1,5 | 2,5 | 2,5 | 2,5 | | | |
| Leiter mm ² max | 4 | 10 | 10 | 10 | | | |