

panel mounting socket outlet, angled - lockable, flange 74x62



Product description	
BALS-Prd.-Nr	12006
EAN	4024941120067
Product category	Panel mounting socket outlet, angled
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	6 h
Voltage	200 - 250V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	blue RAL 5015
Colour of appliance	Hinged lid blue RAL 5015, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	77mm
Width	62mm
Depth	74mm
Flange size vertical in mm	74mm
Flange size horizontal in mm	62mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	52mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	The inclination is 20°
	Lockable with padlock bow diameter 5 mm

Logistics data	
Weight/pcs	0.105 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941120067
Length	74 mm
Width	62 mm
Height	77 mm
Weight	0.106 kg
Volume	353.276 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941820295
Length	207 mm
Width	162 mm
Height	142 mm
Weight	1.15 kg
Volume	3,750 ccm