

## Panel mounting socket outlet angled TN - flange 85x85 fixing centers 70x70



| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 12087   |
| EAN                       | 4024941120876   |
| Product category          | TN panel mounting socket outlet QUICK-CONNECT, angled |
| Current                   | 32A   |
| Number of poles           | 5p  |
| Arrangement of phases     | 3p+N+PE   |
| Position of earth contact | 6 h   |
| Voltage                   | 200/346 - 240/415V~                                   |

| Product description            |   |
|--------------------------------|---|
| Frequency                      | 50/60Hz   |
| VG-type-no.:                   | VG 96919 BS 005   |
| Supply no.:                    | 5935-12-306-7781  |
| Protection degree              | IP67  |
| Colour code                    | bronze-green RAL 6031-F9  |
| Colour of appliance            | Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9, Enclosure grey RAL 7035 |
| Connection design              | screwless spring terminals with KONTEX-contact  |
| Maximum conductor size         | 10,0 qmm  |
| Cable entry                    | other   |
| Height                         | 110mm   |
| Width                          | 101.5mm   |
| Depth                          | 119mm   |
| Flange size vertical in mm     | 85mm  |
| Flange size horizontal in mm   | 85mm  |
| Drill hole dist. vertical mm   | 70mm  |
| Drill hole dist. horizontal mm | 70mm  |
| Material of enclosure          | Polyamide   |
| Contacts                       | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                                |

| Additional technical information |                             |
|----------------------------------|-----------------------------|
|                                  | The inclination is 20°      |
|                                  | With bayonet cover on strap |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.298 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |
| EAN            | 4024941120876    |
| Length         | 119 mm           |
| Width          | 101.5 mm         |
| Height         | 110 mm           |
| Weight         | 0.299 kg         |
| Volume         | 1,328.635 ccm    |
| Packaging      | Carton           |
| Content amount | 10 ST            |
| EAN            | 4024941963343    |
| Length         | 122 mm           |
| Width          | 222 mm           |
| Height         | 538 mm           |
| Weight         | 3.318 kg         |
| Volume         | 14,332.32 ccm    |



4 MB 124

| Ampere                     | 16   | 16   | 16   | 32   | 32   | 32   |
|----------------------------|------|------|------|------|------|------|
| Polzahl                    | 3    | 4    | 5    | 3    | 4    | 5    |
| a                          | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| b                          | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| c                          | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| d                          | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 | 70,0 |
| e ø                        | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  |
| f                          | 8,0  | 8,0  | 8,0  | 8,0  | 8,0  | 8,0  |
| h                          | 46,0 | 46,0 | 46,0 | 50,0 | 50,0 | 50,0 |
| i                          | 57,0 | 57,0 | 60,0 | 67,0 | 67,0 | 69,0 |
| l ø                        | 57,0 | 65,0 | 70,0 | 78,0 | 78,0 | 78,0 |
| α                          | 20°  | 20°  | 20°  | 20°  | 20°  | 20°  |
| Leiter mm <sup>2</sup> min | 1,5  | 1,5  | 1,5  | 2,5  | 2,5  | 2,5  |
| Leiter mm <sup>2</sup> max | 4,0  | 4,0  | 4,0  | 10,0 | 10,0 | 10,0 |