

panel mounting socket outlet, angled - flange 75x75,
fixing centers 60x60



Product description	
BALS-Prd.-Nr	1212
EAN	4024941012126
Product category	Panel mounting socket outlet, angled, Panel mounting socket outlet, angled
Current	16A, 16A
Number of poles	5p, 5p
Arrangement of phases	3p+N+PE, 3p+N+PE
Position of earth contact	6 h, 6 h
Voltage	200/346 - 240/415V~, 200/346 - 240/415V~

Product description	
Frequency	50/60Hz, 50/60Hz
Protection degree	IP44, IP44
Colour code	red RAL 3000, red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035, Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	with screw terminal, with screw terminal
Maximum conductor size	4,0 qmm, 4,0 qmm
Cable entry	other, other
Height	89mm, 89mm
Width	75mm, 75mm
Depth	100mm, 100mm
Flange size vertical in mm	75mm, 75mm
Flange size horizontal in mm	75mm, 75mm
Drill hole dist. vertical mm	60mm, 60mm
Drill hole dist. horizontal mm	60mm, 60mm
Material of enclosure	Polyamide, Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass, The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	The inclination is 20°, The inclination is 20°

Logistics data	
Weight/pcs	0.159 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941012126
Length	100 mm
Width	75 mm
Height	89 mm
Weight	0.16 kg
Volume	667.5 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941959957
Length	245 mm
Width	177 mm
Height	185 mm
Weight	1.723 kg
Volume	7,140 ccm