

Panel mounting socket outlet angled - flange 114x114 fixing centers 90x90



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 12160 |
| EAN | 4024941121606 |
| Product category | TE panel mounting socket outlet, angled |
| Current | 63A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 - 240/415V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 25.0 qmm |
| Cable entry | other |
| Height | 125mm |
| Width | 114mm |
| Depth | 147mm |
| Flange size vertical in mm | 114mm |
| Flange size horizontal in mm | 114mm |
| Drill hole dist. vertical mm | 90mm |
| Drill hole dist. horizontal mm | 90mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 15° |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.573 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941121606 |
| Length | 147 mm |
| Width | 114 mm |
| Height | 125 mm |
| Weight | 0.574 kg |
| Volume | 2,094.75 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941820448 |
| Length | 295 mm |
| Width | 185 mm |
| Height | 215 mm |
| Weight | 3.029 kg |
| Volume | 9,975 ccm |



| Ampere | 63 | 63 | 63 | | | |
|----------------------------|-------|-------|-------|--|--|--|
| Polzahl | 3 | 4 | 5 | | | |
| a | 114,0 | 114,0 | 114,0 | | | |
| b | 114,0 | 114,0 | 114,0 | | | |
| c | 90,0 | 90,0 | 90,0 | | | |
| d | 90,0 | 90,0 | 90,0 | | | |
| e \varnothing | 6,5 | 6,5 | 6,5 | | | |
| f | 12,0 | 12,0 | 12,0 | | | |
| h | 65,0 | 65,0 | 65,0 | | | |
| i | 80,0 | 80,0 | 80,0 | | | |
| k | 92,0 | 92,0 | 92,0 | | | |
| l | 92,0 | 92,0 | 92,0 | | | |
| Leiter mm ² min | 6 | 6 | 6 | | | |
| Leiter mm ² max | 25 | 25 | 25 | | | |