

## Panel mounting socket outlet angled - flange 100x92 fixing centers 85x77



| Product description       |                                      |
|---------------------------|--------------------------------------|
| BALS-Prd.-Nr              | 12568                                |
| EAN                       | 4024941125680                        |
| Product category          | Panel mounting socket outlet, angled |
| Current                   | 63A                                  |
| Number of poles           | 5p                                   |
| Arrangement of phases     | 3p+N+PE                              |
| Position of earth contact | 9 h                                  |
| Voltage                   | 120/208 - 144/250V~                  |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50/60Hz  |
| Protection degree              | IP44   |
| Colour code                    | blue RAL 5015  |
| Colour of appliance            | Hinged lid blue RAL 5015, Enclosure grey RAL 7035  |
| Connection design              | screw terminal as box terminal with Kontex-contact   |
| Maximum conductor size         | 25.0 qmm   |
| Cable entry                    | other  |
| Height                         | 114mm  |
| Width                          | 95mm   |
| Depth                          | 147mm  |
| Flange size vertical in mm     | 100mm  |
| Flange size horizontal in mm   | 92mm   |
| Drill hole dist. vertical mm   | 85mm   |
| Drill hole dist. horizontal mm | 77mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information |                        |
|----------------------------------|------------------------|
|                                  | The inclination is 15° |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.47 kg / Piece |
| Packaging      | Bag             |
| Content amount | 1 ST            |
| EAN            | 4024941125680   |
| Length         | 147 mm          |
| Width          | 95 mm           |
| Height         | 114 mm          |
| Weight         | 0.471 kg        |
| Volume         | 1,592.01 ccm    |
| Packaging      | Carton          |
| Content amount | 10 ST           |
| EAN            | 4024941820714   |
| Length         | 325 mm          |
| Width          | 217 mm          |
| Height         | 210 mm          |
| Weight         | 4.906 kg        |
| Volume         | 13,588.4 ccm    |



| Ampere                     | 63    | 63    | 63    |  |  |  |
|----------------------------|-------|-------|-------|--|--|--|
| Polzahl                    | 3     | 4     | 5     |  |  |  |
| a                          | 100,0 | 100,0 | 100,0 |  |  |  |
| b                          | 92,0  | 92,0  | 92,0  |  |  |  |
| c                          | 85,0  | 85,0  | 85,0  |  |  |  |
| d                          | 77,0  | 77,0  | 77,0  |  |  |  |
| e ø                        | 6,5   | 6,5   | 6,5   |  |  |  |
| f                          | 12,0  | 12,0  | 12,0  |  |  |  |
| h                          | 65,0  | 65,0  | 65,0  |  |  |  |
| i                          | 81,0  | 81,0  | 81,0  |  |  |  |
| k                          | 80,0  | 80,0  | 80,0  |  |  |  |
| l                          | 92,0  | 92,0  | 92,0  |  |  |  |
| Leiter mm <sup>2</sup> min | 6     | 6     | 6     |  |  |  |
| Leiter mm <sup>2</sup> max | 25    | 25    | 25    |  |  |  |