

# Panel mounting socket outlet angled - flange 75x75 fixing centers 60x60



Product description	
BALS-Prd.-Nr	1261
EAN	4024941012614
Product category	Panel mounting socket outlet, angled
Current	16A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	96mm
Width	86mm
Depth	90mm
Flange size vertical in mm	75mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass

Additional technical information	
	The inclination is 20°

Logistics data	
Weight/pcs	0.197 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941012614
Length	90 mm
Width	86 mm
Height	96 mm
Weight	0.198 kg
Volume	743.04 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941818544
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.103 kg
Volume	7,140 ccm