

panel mounting socket outlet, angled - flange 87x71,
fixing centers 70x52



Product description	
BALS-Prd.-Nr	128
EAN	4024941001281
Product category	Panel mounting socket outlet, angled
Current	16A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	90mm
Width	71mm
Depth	96mm
Flange size vertical in mm	87mm
Flange size horizontal in mm	71mm
Drill hole dist. vertical mm	70mm
Drill hole dist. horizontal mm	52mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass

Additional technical information	
	The inclination is 20°

Logistics data	
Weight/pcs	0.165 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941001281
Length	96 mm
Width	71 mm
Height	90 mm
Weight	0.166 kg
Volume	613.44 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941959643
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.775 kg
Volume	5,737.5 ccm