

panel mounting socket outlet, angled - flange 100x92,
fixing centers 85x77



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 12850 |
| EAN | 4024941128506 |
| Product category | Panel mounting socket outlet Quick-Connect, angled |
| Current | 32A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 10 h |
| Voltage | > 50V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 100 - 300Hz |
| Protection degree | IP67 |
| Colour code | green RAL 6002 |
| Colour of appliance | Hinged lid green RAL 6002, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035 |
| Connection design | screwless spring terminals with Kontex-Kontakt |
| Maximum conductor size | 10,0 qmm |
| Cable entry | other |
| Height | 110mm |
| Width | 94mm |
| Depth | 122mm |
| Flange size vertical in mm | 100mm |
| Flange size horizontal in mm | 92mm |
| Drill hole dist. vertical mm | 85mm |
| Drill hole dist. horizontal mm | 77mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of polyamide, The contacts are brass |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 20° |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.275 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941128506 |
| Length | 124 mm |
| Width | 94 mm |
| Height | 110 mm |
| Weight | 0.276 kg |
| Volume | 1,282.16 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941830683 |
| Length | 295 mm |
| Width | 185 mm |
| Height | 215 mm |
| Weight | 2.911 kg |
| Volume | 9,975 ccm |



| Ampere | 16 | 16 | 16 | 32 | 32 | 32 |
|----------------|------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 74,0 | 100,0 | 100,0 | 100,0 | 100,0 | 100,0 |
| b | 62,0 | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 |
| c | 60,0 | 85,0 | 85,0 | 85,0 | 85,0 | 85,0 |
| d | 52,0 | 77,0 | 77,0 | 77,0 | 77,0 | 77,0 |
| e ø | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 | 5,5 |
| f | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 | 8,0 |
| h | 46,0 | 46,0 | 46,0 | 55,0 | 55,0 | 55,0 |
| i | 57,0 | 57,0 | 60,0 | 65,0 | 65,0 | 69,0 |
| k | 57,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| l | 52,0 | 65,0 | 70,0 | 75,0 | 75,0 | 78,0 |
| α | 20° | 20° | 20° | 20° | 20° | 20° |
| Leiter mm² min | 1,5 | 1,5 | 1,5 | 2,5 | 2,5 | 2,5 |
| Leiter mm² max | 4 | 4 | 4 | 10 | 10 | 10 |