

Panel mounting socket outlet straight - flange 60x60 fixing centers 50-52x50-52



Product description	
BALS-Prd.-Nr	13017
EAN	4024941130172
Product category	Panel mounting socket outlet, straight
Current	16A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	80mm
Width	60mm
Depth	79mm
Flange size vertical in mm	60mm
Flange size horizontal in mm	60mm
Drill hole dist. vertical mm	51mm
Drill hole dist. horizontal mm	51mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass

Logistics data	
Weight/pcs	0.128 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941130172
Length	79 mm
Width	60 mm
Height	80 mm
Weight	0.129 kg
Volume	379.2 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941821155
Length	207 mm
Width	162 mm
Height	142 mm
Weight	1.38 kg
Volume	3,750 ccm