

## Panel mounting socket outlet straight - for reefer containers flange 75x75




Product description	
BALS-Prd.-Nr	13021
EAN	4024941130219
Product category	TE panel mounting socket outlet, straight
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	3 h
Voltage	380V~(50Hz) 440V~(60Hz) for reefer containers only

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	other
Height	100mm
Width	93.5mm
Depth	100.4mm
Flange size vertical in mm	75mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.252 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941130219
Length	100.4 mm
Width	93.5 mm
Height	100 mm
Weight	0.253 kg
Volume	938.74 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941968706
Length	295 mm
Width	185 mm
Height	215 mm
Weight	2.684 kg
Volume	9,975 ccm



4 MB 71