

panel mounting socket outlet, straight - flange 73,5x73,5  
fixing centers 60x60, hole diameter 5,5



Product description	
BALS-Prd.-Nr	13038
EAN	4024941130387
Product category	Panel mounting socket outlet, straight
Current	16A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	86mm
Width	73.5mm
Depth	67mm
Flange size vertical in mm	73.5mm
Flange size horizontal in mm	73.5mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass

Logistics data	
Weight/pcs	0.15 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941130387
Length	67 mm
Width	73.5 mm
Height	86 mm
Weight	0.151 kg
Volume	423.507 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941821193
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.625 kg
Volume	5,737.5 ccm