

panel mounting socket outlet, straight - flange 56x56,
fixing centers 44x44



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 131 |
| EAN | 4024941001311 |
| Product category | Panel mounting socket outlet, straight |
| Current | 16A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 6 h |
| Voltage | 200 - 250V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Hinged lid blue RAL 5015, Enclosure grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 71mm |
| Width | 56mm |
| Depth | 67mm |
| Flange size vertical in mm | 56mm |
| Flange size horizontal in mm | 56mm |
| Drill hole dist. vertical mm | 44mm |
| Drill hole dist. horizontal mm | 44mm |
| Material of enclosure | Polyamide |
| Contacts | The contact carrier is made of polyamide, The contacts are brass |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.08 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941001311 |
| Length | 67 mm |
| Width | 56 mm |
| Height | 71 mm |
| Weight | 0.081 kg |
| Volume | 266.392 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941959674 |
| Length | 207 mm |
| Width | 162 mm |
| Height | 142 mm |
| Weight | 0.9 kg |
| Volume | 3,750 ccm |