

Panel mounting socket outlet - TN - flange 107x100 fixing centers 85x77



| Product description | |
|---------------------------|---|
| BALS-Prd.-Nr | 13186 |
| EAN | 4024941131865 |
| Product category | TN panel mounting socket outlet, straight |
| Current | 63A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 6 h |
| Voltage | 200 - 250V~ |

| Product description | |
|--------------------------------|--|
| Frequency | 50/60Hz |
| VG-type-no.: | VG 96919 AS 047 |
| Protection degree | IP67 |
| Colour code | bronze-green RAL 6031-F9 |
| Colour of appliance | Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 25.0 qmm |
| Cable entry | other |
| Height | 114mm |
| Width | 111mm |
| Depth | 139mm |
| Flange size vertical in mm | 107mm |
| Flange size horizontal in mm | 100mm |
| Drill hole dist. vertical mm | 85mm |
| Drill hole dist. horizontal mm | 77mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--------------------|
| | with pilot contact |

| Additional technical information | |
|----------------------------------|-----------------------------|
| | With bayonet cover on strap |

| Logistics data | |
|----------------|----------------|
| Weight/pcs | 0.5 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941131865 |
| Length | 139 mm |
| Width | 111 mm |
| Height | 114 mm |
| Weight | 0.501 kg |
| Volume | 1,758.906 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941838344 |
| Length | 295 mm |
| Width | 185 mm |
| Height | 215 mm |
| Weight | 2.661 kg |
| Volume | 9,975 ccm |



4 MB 134

| Ampere | 63 | 63 | 63 | 125 | 125 | 125 |
|----------------------------|-------|-------|-------|-------|-------|-------|
| Polzahl | 3 | 4 | 5 | 3 | 4 | 5 |
| a | 107,0 | 107,0 | 107,0 | 120,0 | 120,0 | 120,0 |
| b | 100,0 | 100,0 | 100,0 | 120,0 | 120,0 | 120,0 |
| c | 85,0 | 85,0 | 85,0 | 100,0 | 100,0 | 100,0 |
| d | 77,0 | 77,0 | 77,0 | 100,0 | 100,0 | 100,0 |
| e ø | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 | 6,5 |
| f | 12,0 | 12,0 | 12,0 | 21,0 | 21,0 | 21,0 |
| h | 57,0 | 57,0 | 57,0 | 50,0 | 50,0 | 50,0 |
| i | 77,0 | 77,0 | 77,0 | 117,0 | 117,0 | 117,0 |
| k | 113,0 | 113,0 | 113,0 | 129,0 | 129,0 | 129,0 |
| l ø | 88,0 | 88,0 | 88,0 | 104,0 | 104,0 | 104,0 |
| m | 8,0 | 8,0 | 8,0 | 6,0 | 6,0 | 6,0 |
| Leiter mm ² min | 6,0 | 6,0 | 6,0 | 25,0 | 25,0 | 25,0 |
| Leiter mm ² max | 25,0 | 25,0 | 25,0 | 70,0 | 70,0 | 70,0 |