

panel mounting socket outlet, straight - 7 poles, flange 75x75




Product description	
BALS-Prd.-Nr	13329
EAN	4024941133296
Product category	Panel mounting socket outlet, straight
Current	32A
Number of poles	7p
Arrangement of phases	6p+PE
Position of earth contact	6 h
Voltage	400V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	10,0 qmm
Cable entry	other
Height	98mm
Width	75mm
Depth	82mm
Flange size vertical in mm	75mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, The contacts are brass

Logistics data	
Weight/pcs	0.269 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941133296
Length	82 mm
Width	75 mm
Height	98 mm
Weight	0.27 kg
Volume	602.7 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941968171
Length	245 mm
Width	177 mm
Height	185 mm
Weight	2.823 kg
Volume	7,140 ccm



4 MB 389

Ampere Polzahl	16	32					
a	75,0	75,0					
b	75,0	75,0					
c	60,0	60,0					
d	60,0	60,0					
e ø	5,5	5,5					
f	7,0	8,0					
h	28,0	38,0					
i	53,0	62,0					
k	85,0	98,0					
l ø	60,0	60,0					
m	11,0	17,0					
Leiter mm ² min	1,5	2,5					
Leiter mm ² max	4	10					