

# panel mounting socket outlet, straight - 7 poles, flange 75x75





| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 13333                                  |
| EAN                       | 4024941133333                          |
| Product category          | Panel mounting socket outlet, straight |
| Current                   | 32A                                    |
| Number of poles           | 7p                                     |
| Arrangement of phases     | 6p+PE                                  |
| Position of earth contact | 6 h                                    |
| Voltage                   | 400V~                                  |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50/60Hz  |
| Protection degree              | IP67   |
| Colour code                    | red RAL 3000   |
| Colour of appliance            | Hinged lid red RAL 3000, Enclosure grey RAL 7035, Bayonet ring grey RAL 7035               |
| Connection design              | with screw terminal  |
| Maximum conductor size         | 10,0 qmm   |
| Cable entry                    | other  |
| Height                         | 105mm  |
| Width                          | 101mm  |
| Depth                          | 83mm   |
| Flange size vertical in mm     | 75mm   |
| Flange size horizontal in mm   | 75mm   |
| Drill hole dist. vertical mm   | 60mm   |
| Drill hole dist. horizontal mm | 60mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | The contacts are brass, The contact carrier is made of high temperature resistant material |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.316 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941133333 |
| Length         | 83 mm         |
| Width          | 101 mm        |
| Height         | 105 mm        |
| Weight         | 0.317 kg      |
| Volume         | 880.215 ccm   |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941969673 |
| Length         | 295 mm        |
| Width          | 185 mm        |
| Height         | 215 mm        |
| Weight         | 3.324 kg      |
| Volume         | 9,975 ccm     |



| Ampere                     | 16   | 32    |  |  |  |  |  |
|----------------------------|------|-------|--|--|--|--|--|
| Polzahl                    | 7    | 7     |  |  |  |  |  |
| a                          | 75,0 | 75,0  |  |  |  |  |  |
| b                          | 75,0 | 75,0  |  |  |  |  |  |
| c                          | 60,0 | 60,0  |  |  |  |  |  |
| d                          | 60,0 | 60,0  |  |  |  |  |  |
| e ø                        | 5,5  | 5,5   |  |  |  |  |  |
| f                          | 7,0  | 8,0   |  |  |  |  |  |
| h                          | 17,0 | 19,0  |  |  |  |  |  |
| i                          | 57,0 | 65,0  |  |  |  |  |  |
| k                          | 93,0 | 106,0 |  |  |  |  |  |
| l ø                        | 55,0 | 60,0  |  |  |  |  |  |
| m                          | 11,5 | 17,0  |  |  |  |  |  |
| Leiter mm <sup>2</sup> min | 1,5  | 2,5   |  |  |  |  |  |
| Leiter mm <sup>2</sup> max | 4    | 10    |  |  |  |  |  |

4 MB 390