

Panel mounting socket outlet straight - flange 72x65 fixing centers 52x52



Product description	
BALS-Prd.-Nr	1360
EAN	4024941013604
Product category	Panel mounting socket outlet, straight
Current	16A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	9 h
Voltage	200 - 250V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	blue RAL 5015
Colour of appliance	Hinged lid blue RAL 5015, Bayonet ring grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	4,0 qmm
Cable entry	other
Height	84mm
Width	79mm
Depth	74mm
Flange size vertical in mm	72mm
Flange size horizontal in mm	65mm
Drill hole dist. vertical mm	52mm
Drill hole dist. horizontal mm	52mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass

Logistics data	
Weight/pcs	0.159 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941013604
Length	74 mm
Width	79 mm
Height	84 mm
Weight	0.16 kg
Volume	491.064 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941965620
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.715 kg
Volume	5,737.5 ccm