

## Panel mounting socket outlet straight - flange 73,5x73,5 fixing centers 60x60 hole diameter 5,5



Product description	
BALS-Prd.-Nr	13655
EAN	4024941136556
Product category	Panel mounting socket outlet QUICK-CONNECT, straight
Current	16A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	6 h
Voltage	200/346 - 240/415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Enclosure grey RAL 7035
Connection design	screwless spring terminals with KONTEX-contact
Maximum conductor size	4,0 qmm
Cable entry	other
Height	85mm
Width	73.5mm
Depth	86.5mm
Flange size vertical in mm	73.5mm
Flange size horizontal in mm	73.5mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass

Logistics data	
Weight/pcs	0.13 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941136556
Length	86.5 mm
Width	73.5 mm
Height	85 mm
Weight	0.131 kg
Volume	540.409 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941964418
Length	245 mm
Width	177 mm
Height	185 mm
Weight	1.433 kg
Volume	7,140 ccm

