

panel mounting socket outlet, straight - flange 75x75,  
fixing centers 60x60




| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 13816   |
| EAN                       | 4024941138161   |
| Product category          | TE panel mounting socket outlet Quick-Connect, straight |
| Current                   | 32A   |
| Number of poles           | 5p  |
| Arrangement of phases     | 3p+N+PE   |
| Position of earth contact | 6 h   |
| Voltage                   | 200/346 - 240/415V~                                     |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 50/60Hz  |
| Protection degree              | IP67   |
| Colour code                    | red RAL 3000   |
| Colour of appliance            | Hinged lid red RAL 3000, Enclosure grey RAL 7035, Bayonet ring grey RAL 7035                             |
| Connection design              | screwless spring terminals with Kontex-Kontakt   |
| Maximum conductor size         | 10,0 qmm   |
| Cable entry                    | other  |
| Height                         | 107mm  |
| Width                          | 102mm  |
| Depth                          | 113mm  |
| Flange size vertical in mm     | 75mm   |
| Flange size horizontal in mm   | 75mm   |
| Drill hole dist. vertical mm   | 60mm   |
| Drill hole dist. horizontal mm | 60mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.288 kg / Piece |
| Packaging      | Bag              |

| Logistics data |               |
|----------------|---------------|
| Content amount | 1 ST          |
| EAN            | 4024941138161 |
| Length         | 113 mm        |
| Width          | 102 mm        |
| Height         | 107 mm        |
| Weight         | 0.289 kg      |
| Volume         | 1,233.282 ccm |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941831444 |
| Length         | 122 mm        |
| Width          | 222 mm        |
| Height         | 538 mm        |
| Weight         | 3.218 kg      |
| Volume         | 14,332.32 ccm |



4 MB 105

| Ampere Polzahl             | 16<br>3 | 16<br>4 | 16<br>5 | 32<br>3 | 32<br>4 | 32<br>5 |
|----------------------------|---------|---------|---------|---------|---------|---------|
| a                          | 75,0    | 75,0    | 75,0    | 75,0    | 75,0    | 75,0    |
| b                          | 75,0    | 75,0    | 75,0    | 75,0    | 75,0    | 75,0    |
| c                          | 60,0    | 60,0    | 60,0    | 60,0    | 60,0    | 60,0    |
| d                          | 60,0    | 60,0    | 60,0    | 60,0    | 60,0    | 60,0    |
| e ø                        | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     | 5,5     |
| f                          | 7,0     | 7,0     | 7,0     | 8,0     | 8,0     | 8,0     |
| h                          | 35,5    | 35,5    | 35,5    | 46,0    | 46,0    | 46,0    |
| i                          | 57,0    | 58,0    | 57,0    | 65,0    | 65,0    | 65,0    |
| k                          | 76,0    | 83,0    | 93,0    | 100,0   | 100,0   | 106,0   |
| l ø                        | 45,0    | 45,0    | 55,0    | 60,0    | 60,0    | 60,0    |
| m                          | 3,5     | 7,0     | 11,5    | 12,0    | 12,0    | 17,0    |
| Leiter mm <sup>2</sup> min | 1,5     | 1,5     | 1,5     | 2,5     | 2,5     | 2,5     |
| Leiter mm <sup>2</sup> max | 4       | 4       | 4       | 10      | 10      | 10      |