

Flush mounting socket outlet - housing dimensions 90x90





| Product description | |
|---------------------------|------------------------------|
| BALS-Prd.-Nr | 1411 |
| EAN | 4024941222327 |
| Product category | Flush mounting socket outlet |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 - 240/415V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|--------------------------------------|
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | white similar to RAL 9016 |
| Connection design | with screw terminal |
| Maximum conductor size | 4,0 qmm |
| Cable entry | other |
| Height | 115mm |
| Width | 105mm |
| Depth | 99mm |
| Dimension of enclosure | 90x90 mm |
| Material of enclosure | ABS + Polycarbonate |
| Contacts | the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | flush mounting (incl. flush socket), Architecture programme TH, hinged lid with labelling field (optional: key lock) |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.313 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941222327 |

| Logistics data | |
|----------------|---------------|
| Length | 99 mm |
| Width | 105 mm |
| Height | 115 mm |
| Weight | 0.314 kg |
| Volume | 2,224.404 ccm |
| Packaging | Carton |
| Content amount | 6 ST |
| EAN | 4024941222624 |
| Length | 370 mm |
| Width | 218 mm |
| Height | 125 mm |
| Weight | 2.051 kg |
| Volume | 9,329.4 ccm |



| Ampere Poles | 16 3 | 16 4 | 16 5 | 32 5 | Schutzk. Domestic |
|----------------------------|---------|---------|---------|---------|----------------------|
| a | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 |
| b | 90,0 | 90,0 | 90,0 | 90,0 | 90,0 |
| c | 92,0 | 92,0 | 92,0 | 92,0 | 92,0 |
| d | 115,0 | 115,0 | 115,0 | 115,0 | 115,0 |
| e | 64,0 | 64,0 | 64,0 | 64,0 | 64,0 |
| f | 35,0 | 35,0 | 35,0 | 35,0 | 35,0 |
| Cond. mm ² min. | 1,0 | 1,0 | 1,0 | 2,5 | 1,0 |
| Cond. mm ² max. | 4,0 | 4,0 | 4,0 | 10 | 2,5 |

4MB464

