

Wall mounting socket outlet fused - housing dimensions 260x160 with mounting rail



Product description	
BALS-Prd.-Nr	15035
EAN	4024941150354
Product category	TE wall mounting socket outlet, fused
Current	63A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Operating window smoky topaz, Hinged lid red RAL 3000, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	25.0 qmm
Cable entry	top entry M40 bottom entry M40/M32
Height	303mm
Width	160mm
Depth	185mm
Dimension of enclosure	260x160 mm (HxW)
Material of enclosure	Polycarbonate
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top and two at bottom open
	With mounting rail, Protective cover for fuses with stamping, With mounting rail for 7 modules, vertical

Logistics data	
Weight/pcs	1.94 kg / Piece

Logistics data	
Packaging	Carton
Content amount	1 ST
EAN	4024941150354
Length	325 mm
Width	217 mm
Height	210 mm
Weight	2.156 kg
Volume	13,588.4 ccm



14 MB 14