

# wall mounting socket outlet, fused - housing dimensions 225x118, with fuse base D 0



| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 15115  |
| EAN                       | 4024941151153                                    |
| Product category          | Quick-Connect wall mounting socket outlet, fused |
| Current                   | 32A  |
| Number of poles           | 4p   |
| Arrangement of phases     | 3P+PE  |
| Position of earth contact | 6 h  |
| Voltage                   | 380 - 415V~                                      |

| Product description    |  |
|------------------------|--|
| Frequency              | 50/60Hz  |
| Protection degree      | IP67   |
| Colour code            | red RAL 3000   |
| Colour of appliance    | Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Housing screws grey RAL 7035, Bayonet ring grey RAL 7035, Housing top grey RAL 7035, Operating window smoky topaz |
| Connection design      | screwless spring terminals with Kontex-Kontakt   |
| Maximum conductor size | 10,0 qmm   |
| Cable entry            | top entry M25/M25 bottom entry M25   |
| Height                 | 260mm  |
| Width                  | 118mm  |
| Depth                  | 144mm  |
| Dimension of enclosure | 225x118 mm (HxW)   |
| Material of enclosure  | Polycarbonate  |
| Contacts               | the contacts are brass nickel plated, The contact carrier is made of polyamide   |

| Additional technical information |  |
|----------------------------------|--|
|                                  | The cable entry is one at top open, one at top is closed, and two at bottom are closed |
|                                  | With fuse base 3 pole D02  |

| Logistics data |                |
|----------------|----------------|
| Weight/pcs     | 0.0 kg / Piece |

| Logistics data |               |
|----------------|---------------|
| Packaging      | Carton        |
| Content amount | 1 ST          |
| EAN            | 4024941151153 |
| Length         | 275 mm        |
| Width          | 175 mm        |
| Height         | 137 mm        |
| Weight         | 0.125 kg      |
| Volume         | 5,737.5 ccm   |



| Ampere  | 16      | 16      | 32      | 32      | 32      |
|---------|---------|---------|---------|---------|---------|
| Polzahl | 4       | 5       | 3       | 4       | 5       |
| a       | 118,0   | 118,0   | 118,0   | 118,0   | 118,0   |
| b       | 225,0   | 225,0   | 225,0   | 225,0   | 225,0   |
| c       | 101,0   | 101,0   | 101,0   | 101,0   | 101,0   |
| d       | 208,0   | 208,0   | 208,0   | 208,0   | 208,0   |
| e       | 127,0   | 134,0   | 143,0   | 143,0   | 149,0   |
| f       | 245,0   | 245,0   | 255,0   | 255,0   | 255,0   |
| g ø     | 6,5     | 6,5     | 6,5     | 6,5     | 6,5     |
| h       | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     |
| i       | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |
| k       | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |