


## wall mounting socket outlet, fused - housing dimensions 260x160 with fuse base D III



Product description	
BALS-Prd.-Nr	15137
EAN	4024941151375
Product category	Wall mounting socket outlet, fused
Current	63A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	red RAL 3000
Colour of appliance	Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Operating window smoky topaz, Housing screws grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	25.0 qmm
Cable entry	top entry M40 bottom entry M40/M32
Height	276mm
Width	184mm
Depth	220mm
Dimension of enclosure	276x184 mm (HxW)
Material of enclosure	Polyester RAL 7035
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical information	
	The cable entry is one at top and two at bottom open
	With fuse base 3 pole D III



14 MB 35

Ampere Polzahl	32 4	32 5	63 4	63 5			
a	184,0	184,0	184,0	184,0			
b	276,0	276,0	276,0	276,0			
c	158,0	158,0	158,0	158,0			
d	250,0	250,0	250,0	250,0			
e	205,0	205,0	220,0	220,0			
f $\varnothing$	11,0	11,0	11,0	11,0			
g	8,5	8,5	8,5	8,5			
h	M40	M40	M40	M40			
i	M40/32	M40/32	M40/32	M40/32			