

wall mounting socket outlet, fused - housing dimensions 260x160, with C-type circuit breaker



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 15142 |
| EAN | 4024941151429 |
| Product category | Quick-Connect wall mounting socket outlet, fused |
| Current | 32A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 6 h |
| Voltage | 380 - 415V~ |

| Product description | |
|------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Operating window smoky topaz, Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035 |
| Connection design | screwless spring terminals with Kontex-Kontakt |
| Maximum conductor size | 10,0 qmm |
| Cable entry | top entry M40 bottom entry M40/M32 |
| Height | 296mm |
| Width | 160mm |
| Depth | 169mm |
| Dimension of enclosure | 260x160 mm (HxW) |
| Material of enclosure | Polycarbonate |
| Contacts | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | The cable entry is one at top and two at bottom open |
| | With 3 pole C-type MCB |

| Logistics data | |
|----------------|----------------|
| Weight/pcs | 0.0 kg / Piece |

| Logistics data | |
|----------------|---------------|
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941151429 |
| Length | 325 mm |
| Width | 217 mm |
| Height | 210 mm |
| Weight | 0.216 kg |
| Volume | 13,588.4 ccm |



14 MB 11

| Ampere | 32 | 32 | 63 | 63 | | |
|---------|--------|--------|--------|--------|--|--|
| Polzahl | 4 | 5 | 4 | 5 | | |
| a | 160,0 | 160,0 | 160,0 | 160,0 | | |
| b | 260,0 | 260,0 | 260,0 | 260,0 | | |
| c | 140,0 | 140,0 | 140,0 | 140,0 | | |
| d | 240,0 | 240,0 | 240,0 | 240,0 | | |
| e | 172,0 | 174,0 | 195,0 | 195,0 | | |
| f | 293,0 | 294,0 | 304,0 | 304,0 | | |
| g ø | 8,1 | 8,1 | 8,1 | 8,1 | | |
| h | 10,0 | 10,0 | 10,0 | 10,0 | | |
| i | M40 | M40 | M40 | M40 | | |
| k | M32/40 | M32/40 | M32/40 | M32/40 | | |
| | | | | | | |
| | | | | | | |