

Wall mounting socket outlet fused - housing dimensions 225x118 with fuse base D II



Product description	
BALS-Prd.-Nr	15179
EAN	4024941151795
Product category	QUICK-CONNECT wall mounting socket outlet, fused
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	7 h
Voltage	480 - 500V~

Product description	
Frequency	50/60Hz
Protection degree	IP67
Colour code	black RAL 9005
Colour of appliance	Hinged lid black RAL 9005, Operating window smoky topaz, Bayonet ring grey RAL 7035, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035
Connection design	screwless spring terminals with KONTEX-contact
Maximum conductor size	10,0 qmm
Cable entry	1xM40 top, 1xM32/M40 bottom
Height	276mm
Width	184mm
Depth	208mm
Dimension of enclosure	276x184 mm (HxW)
Material of enclosure	Polyester RAL 7035
Contacts	the contact carrier is made of polyamide, the contacts are brass

Additional technical information	
	cable entry two at top and two at bottom (open)
	With fuse base 3 pole D II

Logistics data	
Weight/pcs	1.916 kg / Piece

Logistics data	
Packaging	Carton
Content amount	1 ST
EAN	4024941151795
Length	335 mm
Width	283 mm
Height	268 mm
Weight	2.266 kg
Volume	21,937.5 ccm