

## wall mounting socket outlet, fused - housing dimensions 260x160 with mounting rail



| Product description       |                                    |
|---------------------------|------------------------------------|
| BALS-Prd.-Nr              | 1599                               |
| EAN                       | 4024941015998                      |
| Product category          | Wall mounting socket outlet, fused |
| Current                   | 32A                                |
| Number of poles           | 5p                                 |
| Arrangement of phases     | 3p+N+PE                            |
| Position of earth contact | 6 h                                |
| Voltage                   | 200/346 - 240/415V~                |

| Product description    |  |
|------------------------|--|
| Frequency              | 50/60Hz  |
| Protection degree      | IP67   |
| Colour code            | red RAL 3000   |
| Colour of appliance    | Hinged lid red RAL 3000, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Operating window smoky topaz, Housing screws grey RAL 7035, Bayonet ring grey RAL 7035 |
| Connection design      | with screw terminal  |
| Maximum conductor size | 10,0 qmm   |
| Cable entry            | top entry M40 bottom entry M40/M32   |
| Height                 | 296mm  |
| Width                  | 160mm  |
| Depth                  | 174mm  |
| Dimension of enclosure | 260x160 mm (HxW)   |
| Material of enclosure  | Polycarbonate  |
| Contacts               | the contacts are brass nickel plated, The contact carrier is made of polyamide   |

| Additional technical information |  |
|----------------------------------|--|
|                                  | The cable entry is one at top and two at bottom open   |
|                                  | With mounting rail, With mounting rail for 7 modules, vertical, Protective cover for fuses with stamping |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 1.765 kg / Piece |

| Logistics data |               |
|----------------|---------------|
| Packaging      | Carton        |
| Content amount | 1 ST          |
| EAN            | 4024941015998 |
| Length         | 325 mm        |
| Width          | 217 mm        |
| Height         | 210 mm        |
| Weight         | 1.981 kg      |
| Volume         | 13,588.4 ccm  |



14 MB 11

| Ampere  | 32     | 32     | 63     | 63     |  |  |  |
|---------|--------|--------|--------|--------|--|--|--|
| Polzahl | 4      | 5      | 4      | 5      |  |  |  |
| a       | 160,0  | 160,0  | 160,0  | 160,0  |  |  |  |
| b       | 260,0  | 260,0  | 260,0  | 260,0  |  |  |  |
| c       | 140,0  | 140,0  | 140,0  | 140,0  |  |  |  |
| d       | 240,0  | 240,0  | 240,0  | 240,0  |  |  |  |
| e       | 172,0  | 174,0  | 195,0  | 195,0  |  |  |  |
| f       | 293,0  | 294,0  | 304,0  | 304,0  |  |  |  |
| g ø     | 8,1    | 8,1    | 8,1    | 8,1    |  |  |  |
| h       | 10,0   | 10,0   | 10,0   | 10,0   |  |  |  |
| i       | M40    | M40    | M40    | M40    |  |  |  |
| k       | M32/40 | M32/40 | M32/40 | M32/40 |  |  |  |
|         |        |        |        |        |  |  |  |
|         |        |        |        |        |  |  |  |