

## wall mounting socket outlet, switched, interlocked - housing dimensions 225x118



| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 16104   |
| EAN                       | 4024941161046   |
| Product category          | TE wall mounting socket outlet, switched, interlocked |
| Current                   | 32A   |
| Number of poles           | 3p  |
| Arrangement of phases     | 2P+PE   |
| Position of earth contact | 6 h   |
| Voltage                   | 200 - 250V~   |

| Product description    |   |
|------------------------|---|
| Frequency              | 50/60Hz   |
| Protection degree      | IP67  |
| Colour code            | blue RAL 5015   |
| Colour of appliance    | Hinged lid blue RAL 5015, Housing bottom grey RAL 7035, Housing screws grey RAL 7035, Bayonet ring grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035 |
| Connection design      | screwless spring terminals with Kontex-Kontakt  |
| Maximum conductor size | 10,0 qmm  |
| Cable entry            | top entry M25/M25 bottom entry M25  |
| Height                 | 260mm   |
| Width                  | 118mm   |
| Depth                  | 144mm   |
| Dimension of enclosure | 225x118 mm (HxW)  |
| Material of enclosure  | Polycarbonate   |
| Contacts               | the contacts are brass nickel plated, The contact carrier is made of polyamide  |

| Additional technical information |  |
|----------------------------------|--|
|                                  | The cable entry is one at top open, one at top is closed, and two at bottom are closed |
|                                  | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm                     |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 1.23 kg / Piece |

| Logistics data |               |
|----------------|---------------|
| Packaging      | Carton        |
| Content amount | 1 ST          |
| EAN            | 4024941161046 |
| Length         | 275 mm        |
| Width          | 175 mm        |
| Height         | 137 mm        |
| Weight         | 1.355 kg      |
| Volume         | 5,737.5 ccm   |



| Ampere  | 16      | 16      | 32      | 32      | 32      |
|---------|---------|---------|---------|---------|---------|
| Polzahl | 4       | 5       | 3       | 4       | 5       |
| a       | 118,0   | 118,0   | 118,0   | 118,0   | 118,0   |
| b       | 225,0   | 225,0   | 225,0   | 225,0   | 225,0   |
| c       | 101,0   | 101,0   | 101,0   | 101,0   | 101,0   |
| d       | 208,0   | 208,0   | 208,0   | 208,0   | 208,0   |
| e       | 127,0   | 134,0   | 143,0   | 143,0   | 149,0   |
| f       | 245,0   | 245,0   | 255,0   | 255,0   | 255,0   |
| g ø     | 6,5     | 6,5     | 6,5     | 6,5     | 6,5     |
| h       | 8,0     | 8,0     | 8,0     | 8,0     | 8,0     |
| i       | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |
| k       | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 | 2 x M25 |