

wall mounting socket outlet, switched, interlocked,  
chemically resistant - housing dimensions 170x90



| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 16916   |
| EAN                       | 4024941169165   |
| Product category          | TE wall mounting socket outlet, switched, interlocked |
| Current                   | 16A   |
| Number of poles           | 5p  |
| Arrangement of phases     | 3p+N+PE   |
| Position of earth contact | 6 h   |
| Voltage                   | 200/346 - 240/415V~                                   |

| Product description    |  |
|------------------------|--|
| Frequency              | 50/60Hz  |
| Protection degree      | IP67   |
| Colour code            | red RAL 3000   |
| Colour of appliance    | Hinged lid red RAL 3000, Bayonet ring lightbeige, Housing bottom lightbeige, Housing top lightbeige, Control knob lightbeige |
| Connection design      | screwless spring terminals with Kontex-Kontakt   |
| Maximum conductor size | 4,0 qmm  |
| Cable entry            | top entry M20 bottom entry M25/20  |
| Height                 | 195mm  |
| Width                  | 90mm   |
| Depth                  | 123mm  |
| Dimension of enclosure | 170x90 mm (HxW)  |
| Material of enclosure  | Polycarbonate+Polyester light - beige  |
| Contacts               | The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated                     |

| Additional technical information |   |
|----------------------------------|---|
|                                  | The cable entry is one at top open and two at bottom closed   |
|                                  | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm, Lower part of housing rotatable by 180° |

| Logistics data |                 |
|----------------|-----------------|
| Weight/pcs     | 0.69 kg / Piece |
| Packaging      | Carton          |
| Content amount | 1 ST            |
| EAN            | 4024941169165   |
| Length         | 124 mm          |
| Width          | 91 mm           |
| Height         | 196 mm          |
| Weight         | 0.75 kg         |
| Volume         | 2,211.664 ccm   |



| Ampere Polzahl | 16<br>3 | 16<br>4 | 16<br>5 |
|----------------|---------|---------|---------|
| a              | 90,0    | 90,0    | 90,0    |
| b              | 170,0   | 170,0   | 170,0   |
| c              | 77,0    | 77,0    | 77,0    |
| d              | 137,5   | 137,5   | 137,5   |
| e              | 108,0   | 115,0   | 121,0   |
| f              | 191,5   | 191,5   | 191,5   |
| g              | 6,0     | 6,0     | 6,0     |
| h ø            | 5,5     | 5,5     | 5,5     |
| i              | M20     | M20     | M20     |
| k              | M20/25  | M20/25  | M20/25  |