

Wall mounting socket outlet switched interlocked and fused - housing dimensions 460x180

Product description	
BALS-Prd.-Nr	17134
EAN	4024941171342
Product category	TE wall mounting socket outlet switched, interlocked, fused
Current	63A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	6 h
Voltage	200 - 250V~
Frequency	50/60Hz
Protection degree	IP44
Colour code	blue RAL 5015
Colour of appliance	Operating window smoky topaz, Hinged lid blue RAL 5015, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035
Connection design	screw terminal as box terminal with Kontex-contact
Maximum conductor size	25.0 qmm
Cable entry	top entry 1x M32 bottom entry 2x M32
Height	500mm
Width	180mm

Product description	
Depth	191mm
Dimension of enclosure	460x180 mm (HxW)
Material of enclosure	Polycarbonate
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Logistics data	
Weight/pcs	3.179 kg / Piece
Packaging	Carton
Content amount	1 ST
EAN	4024941171342
Length	560 mm
Width	215 mm
Height	260 mm
Weight	3.641 kg
Volume	26,400 ccm