

Wall mounting socket outlet switched interlocked and fused - housing dimensions 365x134 with C-type circuit breaker



| Product description | |
|---------------------------|-------------------------------------------------------------|
| BALS-Prd.-Nr | 17193 |
| EAN | 4024941171939 |
| Product category | TE wall mounting socket outlet switched, interlocked, fused |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |

| Product description | |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Voltage | 200/346 - 240/415V~ |
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | red RAL 3000 |
| Colour of appliance | Operating window smoky topaz, Hinged lid red RAL 3000, Bayonet ring grey RAL 7035, Housing screws grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035, Control knob grey RAL 7035 |
| Connection design | screwless spring terminals with KONTEX-contact |
| Maximum conductor size | 4,0 qmm |
| Cable entry | top entry M32/M25 bottom entry M32/M25 |
| Height | 390mm |
| Width | 134mm |
| Depth | 153mm |
| Dimension of enclosure | 365x134 mm (HxW) |
| Material of enclosure | Polycarbonate |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--------------------------------------------------------------------|
| | cable entry two at top and two at bottom (open) |
| | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm |
| | With 3 pole C-type MCB |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 2.062 kg / Piece |
| Packaging | Carton |
| Content amount | 1 ST |
| EAN | 4024941171939 |
| Length | 387 mm |
| Width | 222 mm |
| Height | 150 mm |
| Weight | 2.255 kg |
| Volume | 11,029.5 ccm |



| Ampere Poles | 16 4 | 16 5 | 32 4 | 32 5 | 63 4 | 63 5 |
|--------------|---------|---------|---------|---------|---------|---------|
| a | 134 | 134 | 134 | 134 | 180 | 180 |
| b | 365 | 365 | 365 | 365 | 460 | 460 |
| c | 117 | 117 | 117 | 117 | 160 | 160 |
| d | 348 | 348 | 348 | 348 | 440 | 440 |
| Øg | 6,5 | 6,5 | 6,5 | 6,5 | 8,3 | 8,3 |
| h | 8 | 8 | 8 | 8 | 6,5 | 6,5 |
| i | M32/25 | M32/25 | M40/32 | M40/32 | M40 | M40 |
| k | M32/25 | M32/25 | M40/32 | M40/32 | M40/32 | M40/32 |
| x | 390 | 390 | 400 | 400 | 503 | 503 |
| y | 134 | 134 | 134 | 134 | 180 | 180 |
| z | 153 | 153 | 154 | 161 | 192 | 192 |