

# Wall mounting socket outlet switched interlocked fused - chemically resistant - housing dimensions 365x134 with C-type MCB and RCCB



| Product description       |   |
|---------------------------|---|
| BALS-Prd.-Nr              | 17669   |
| EAN                       | 4024941176699   |
| Product category          | TE wall mounting socket outlet switched, interlocked, fused |
| Current                   | 16A   |
| Number of poles           | 5p  |
| Arrangement of phases     | 3p+N+PE   |
| Position of earth contact | 6 h   |

| Product description    |  |
|------------------------|--|
| Voltage                | 200/346 - 240/415V~  |
| Frequency              | 50/60Hz  |
| Protection degree      | IP67   |
| Colour code            | red RAL 3000   |
| Colour of appliance    | Bayonet ring lightbeige, Housing top lightbeige, Hinged lid red RAL 3000, Housing bottom lightbeige, Operating window lightbeige, Control knob lightbeige, Housing screws lightbeige |
| Connection design      | screwless spring-clamp technology  |
| Maximum conductor size | 4,0 qmm  |
| Cable entry            | top entry M32/M25 bottom entry M32/M25   |
| Height                 | 390mm  |
| Width                  | 134mm  |
| Depth                  | 153mm  |
| Dimension of enclosure | 365x134 mm (HxW)   |
| Material of enclosure  | Polycarbonate+Polyester light - beige  |
| Contacts               | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated   |

| Additional technical information |  |
|----------------------------------|--|
|                                  | cable entry two at top and two at bottom (open)                    |
|                                  | In 0-position lockable for 3 padlocks with bow diameter up to 7 mm |
|                                  | With 4 pole 25/0.03A RCCB, With 3 pole C-type MCB                  |

| Logistics data |                |
|----------------|----------------|
| Weight/pcs     | 0.0 kg / Piece |
| Packaging      | Carton         |
| Content amount | 1 ST           |
| EAN            | 4024941176699  |
| Length         | 387 mm         |
| Width          | 222 mm         |
| Height         | 150 mm         |
| Weight         | 0.193 kg       |
| Volume         | 11,029.5 ccm   |



| Ampere Poles | 16<br>4 | 16<br>5 | 32<br>4 | 32<br>5 | 63<br>4 | 63<br>5 |
|--------------|---------|---------|---------|---------|---------|---------|
| a            | 134     | 134     | 134     | 134     | 180     | 180     |
| b            | 365     | 365     | 365     | 365     | 460     | 460     |
| c            | 117     | 117     | 117     | 117     | 160     | 460     |
| d            | 348     | 348     | 348     | 348     | 440     | 440     |
| Øg           | 6,5     | 6,5     | 6,5     | 6,5     | 8,3     | 8,3     |
| h            | 8       | 8       | 8       | 8       | 6,5     | 6,5     |
| i            | M32/25  | M32/25  | M40/32  | M40/32  | M40     | M40     |
| k            | M32/25  | M32/25  | M40/32  | M40/32  | M40/32  | M40/32  |
| x            | 390     | 390     | 400     | 400     | 503     | 503     |
| y            | 134     | 134     | 134     | 134     | 180     | 180     |
| z            | 153     | 153     | 154     | 161     | 192     | 192     |