

plug - with screwless terminals, for harsh applications



Product description	
BALS-Prd.-Nr	211002
EAN	4024941196383
Product category	QUICK-CONNECT TE plug
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	12 h
Voltage	> 50V~ power supply after isolating transformer
Frequency	50/60Hz

Product description	
Protection degree	IP44
Colour code	grey RAL 7035
Colour of appliance	Collar grey RAL 7035, Housing cover grey RAL 7035, Cable gland grey RAL 7035
Connection design	screwless spring-clamp technology
Maximum conductor size	2,5 qmm
Cable entry	with cable gland
Height	147mm
Width	51mm
Depth	59mm
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of high temperature resistant material

Logistics data	
Weight/pcs	0.125 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941196383
Length	59 mm
Width	51 mm
Height	147 mm
Weight	0.126 kg

Logistics data	
Volume	442.323 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941842594
Length	248 mm
Width	158 mm
Height	123 mm
Weight	1.347 kg
Volume	3,960 ccm