

plug - with screwless terminals



| Product description | |
|---------------------------|--------------------|
| BALS-Prd.-Nr | 2126 |
| EAN | 4024941021265 |
| Product category | QUICK-CONNECT plug |
| Current | 16A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 6 h |
| Voltage | 200 - 250V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP44 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Collar blue RAL 5015, Housing cover blue RAL 5015, Cable gland grey RAL 7035 |
| Connection design | screwless spring-clamp technology |
| Maximum conductor size | 2,5 qmm |
| Cable entry | with cable gland |
| Height | 134mm |
| Width | 53mm |
| Depth | 62mm |
| Material of enclosure | Polyamide |
| Contacts | The contacts are brass, The contact carrier is made of polyamide |

| Additional technical information | |
|----------------------------------|---|
| | Screwless housing connection with snap fastening, For cable diameter from 8 up to max. 18 mm, Multi-Grip cable gland with gasket and integrated strain relief |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.128 kg / Piece |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941958028 |

| Logistics data | |
|----------------|-------------|
| Length | 275 mm |
| Width | 175 mm |
| Height | 137 mm |
| Weight | 1.405 kg |
| Volume | 5,737.5 ccm |

