

## Wall mounting appliance inlet - with closure cap



Product description	
BALS-Prd.-Nr	24089
EAN	4024941240895
Product category	Wall mounting appliance inlet
Current	32A
Number of poles	5p
Arrangement of phases	3p+N+PE
Position of earth contact	7 h
Voltage	277/480 - 288/500V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	black RAL 9005
Colour of appliance	Collar black RAL 9005, Closure cap grey RAL 7035, Bayonet ring grey RAL 7035, Housing bottom grey RAL 7035, Housing top grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	6,0 qmm
Cable entry	top entry M25
Height	148mm
Width	100mm
Depth	125mm
Dimension of enclosure	75x90 mm (HxW)
Material of enclosure	Polyamide
Contacts	the contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top open and one rear sided closed
	With closure cap

Logistics data	
Weight/pcs	0.409 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941240895
Length	125 mm
Width	100 mm
Height	148 mm
Weight	0.41 kg
Volume	1,850 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941832908
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.316 kg
Volume	17,062.5 ccm

