

Wall mounting appliance inlet - housing dimensions 100x75



| Product description | |
|---------------------------|-------------------------------|
| BALS-Prd.-Nr | 2415 |
| EAN | 4024941024150 |
| Product category | Wall mounting appliance inlet |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 6 h |
| Voltage | 200/346 - 240/415V~ |

| Product description | |
|------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP44 |
| Colour code | red RAL 3000 |
| Colour of appliance | Housing top red RAL 3000, Housing bottom grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 2,5 qmm |
| Cable entry | top entry M20 |
| Height | 135mm |
| Width | 75mm |
| Depth | 110mm |
| Dimension of enclosure | 100x75 mm (HxW) |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of polyamide, the contacts are brass |

| Additional technical information | |
|----------------------------------|---|
| | The cable entry is one at top open and one at bottom and one rear side closed |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.249 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941024150 |
| Length | 110 mm |
| Width | 75 mm |
| Height | 135 mm |
| Weight | 0.25 kg |
| Volume | 1,113.75 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941827904 |
| Length | 387 mm |
| Width | 222 mm |
| Height | 150 mm |
| Weight | 2.683 kg |
| Volume | 11,029.5 ccm |

