

wall mounting appliance inlet - with closure cap



Product description	
BALS-Prd.-Nr	2484
EAN	4024941024846
Product category	Wall mounting appliance inlet
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Position of earth contact	4 h
Voltage	100 - 130V~
Frequency	50/60Hz

Product description	
Protection degree	IP67
Colour code	yellow RAL 1012
Colour of appliance	Housing bottom grey RAL 7035, Closure cap grey RAL 7035, Housing top grey RAL 7035, Collar yellow RAL 1012, Bayonet ring grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	2,5 qmm
Cable entry	top entry M20
Height	138mm
Width	70mm
Depth	112mm
Dimension of enclosure	87x64 mm (HxW)
Material of enclosure	Polyamide
Contacts	the contacts are brass nickel plated, The contact carrier is made of polyamide

Additional technical information	
	The cable entry is one at top open and one at bottom and one rear side closed
	With closure cap

Logistics data	
Weight/pcs	0.242 kg / Piece
Packaging	Bag

Logistics data	
Content amount	1 ST
EAN	4024941024846
Length	112 mm
Width	70 mm
Height	138 mm
Weight	0.243 kg
Volume	1,081.92 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941832816
Length	325 mm
Width	217 mm
Height	210 mm
Weight	2.626 kg
Volume	13,588.4 ccm

