

Connector - with screw terminals one piece housing



| Product description | |
|---------------------------|--------------------------------------|
| BALS-Prd.-Nr | 310344 |
| EAN | 4024941097239 |
| Product category | TLS connector MULTI-GRIP cable gland |
| Current | 16A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 4 h |
| Voltage | 57/100 - 75/130V~ |
| Frequency | 50/60Hz |

| Product description | |
|------------------------|--|
| Protection degree | IP67 |
| Colour code | yellow RAL 1012 |
| Colour of appliance | Hinged lid yellow RAL 1012, Enclosure yellow RAL 1012, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 2,5 qmm |
| Cable entry | with cable gland |
| Height | 160mm |
| Width | 87mm |
| Depth | 92mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of polyamide, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | one piece housing, MULTI-GRIP cable gland with gasket and integrated strain relief, For cable diameter from 8 up to max. 18 mm |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.24 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941097239 |

| Logistics data | |
|----------------|---------------|
| Length | 92 mm |
| Width | 87 mm |
| Height | 160 mm |
| Weight | 0.241 kg |
| Volume | 1,280.64 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941834964 |
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 2.533 kg |
| Volume | 7,140 ccm |

