

Connector - with screwless terminals for harsh applications



| Product description | |
|---------------------------|----------------------------|
| BALS-Prd.-Nr | 310417 |
| EAN | 4024941106955 |
| Product category | QUICK-CONNECT TE connector |
| Current | 16A |
| Number of poles | 3p |
| Arrangement of phases | 2P+PE |
| Position of earth contact | 2 h |
| Voltage | > 50V~ |

| Product description | |
|------------------------|--|
| Frequency | > 300 - 500Hz |
| Protection degree | IP67 |
| Colour code | green RAL 6002 |
| Colour of appliance | Hinged lid green RAL 6002, Enclosure green RAL 6002, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035 |
| Connection design | screwless spring terminals with KONTEX-contact |
| Maximum conductor size | 2,5 qmm |
| Cable entry | with cable gland |
| Height | 163mm |
| Width | 71mm |
| Depth | 77mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|---|
| | For cable diameter from 8 up to max. 18 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|------------------|
| Weight/pcs | 0.195 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |

| Logistics data | |
|----------------|---------------|
| EAN | 4024941106955 |
| Length | 77 mm |
| Width | 71 mm |
| Height | 163 mm |
| Weight | 0.196 kg |
| Volume | 891.121 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941835237 |
| Length | 245 mm |
| Width | 177 mm |
| Height | 185 mm |
| Weight | 2.083 kg |
| Volume | 7,140 ccm |

