

Connector - with screwless terminals for harsh applications



| Product description | |
|---------------------------|----------------------------|
| BALS-Prd.-Nr | 31314 |
| EAN | 4024941313148 |
| Product category | QUICK-CONNECT TE connector |
| Current | 32A |
| Number of poles | 5p |
| Arrangement of phases | 3p+N+PE |
| Position of earth contact | 9 h |
| Voltage | 120/208 - 144/250V~ |

| Product description | |
|------------------------|--|
| Frequency | 50/60Hz |
| Protection degree | IP67 |
| Colour code | blue RAL 5015 |
| Colour of appliance | Enclosure blue RAL 5015, Hinged lid blue RAL 5015, Bayonet ring grey RAL 7035, Cable gland grey RAL 7035 |
| Connection design | screwless spring terminals with KONTEX-contact |
| Maximum conductor size | 6,0 qmm |
| Cable entry | with cable gland |
| Height | 196mm |
| Width | 101.5mm |
| Depth | 106mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | For cable diameter from 13 up to max. 27 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.42 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941313148 |
| Length | 106 mm |
| Width | 101.5 mm |
| Height | 196 mm |
| Weight | 0.421 kg |
| Volume | 2,108.764 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941828109 |
| Length | 330 mm |
| Width | 216 mm |
| Height | 260 mm |
| Weight | 4.426 kg |
| Volume | 17,062.5 ccm |

