

Connector - with TE screw terminals for harsh applications



| Product description | |
|---------------------------|---------------|
| BALS-Prd.-Nr | 31611 |
| EAN | 4024941316118 |
| Product category | TE connector |
| Current | 125A |
| Number of poles | 4p |
| Arrangement of phases | 3P+PE |
| Position of earth contact | 10 h |
| Voltage | > 50V~ |

| Product description | |
|------------------------|---|
| Frequency | 100 - 300Hz |
| Protection degree | IP67 |
| Colour code | green RAL 6002 |
| Colour of appliance | Hinged lid green RAL 6002, Bayonet ring grey RAL 7035, Housing cover grey RAL 7035, Cable gland grey RAL 7035, Collar grey RAL 7035 |
| Connection design | screw terminal as box terminal with Kontex-contact |
| Maximum conductor size | 50.0 qmm |
| Cable entry | with cable gland |
| Height | 295mm |
| Width | 125mm |
| Depth | 128mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|--|
| | For cable diameter from 26 up to max. 50 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 1.21 kg / Piece |
| Packaging | Bag |

| Logistics data | |
|----------------|---------------|
| Content amount | 1 ST |
| EAN | 4024941316118 |
| Length | 128 mm |
| Width | 125 mm |
| Height | 295 mm |
| Weight | 1.211 kg |
| Volume | 4,720 ccm |
| Packaging | Carton |
| Content amount | 5 ST |
| EAN | 4024941835404 |
| Length | 345 mm |
| Width | 345 mm |
| Height | 217 mm |
| Weight | 6.385 kg |
| Volume | 24,276 ccm |

