

## Connector TN - with cable gland with bayonet cover



Product description	
BALS-Prd.-Nr	31866
EAN	4024941318662
Product category	QUICK-CONNECT TN connector
Current	32A
Number of poles	4p
Arrangement of phases	3P+PE
Position of earth contact	6 h
Voltage	380 - 415V~
Frequency	50/60Hz

Product description	
VG-type-no.:	VG 96919 DS 023
Protection degree	IP67
Colour code	bronze-green RAL 6031-F9
Colour of appliance	Cable gland bronze-green RAL 6031-F9, Bayonet ring bronze-green RAL 6031-F9, Hinged lid bronze-green RAL 6031-F9, Enclosure bronze-green RAL 6031-F9
Connection design	screwless spring terminals with KONTEX-contact
Maximum conductor size	6,0 qmm
Cable entry	with cable gland
Height	200mm
Width	94mm
Depth	96.5mm
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	For cable diameter from 11 up to max. 23,5 mm, MULTI-GRIP cable gland with gasket, integrated cable clamp and additional water evacuation openings
	With bayonet cover on strap

Logistics data	
Weight/pcs	0.341 kg / Piece

Logistics data	
Packaging	Bag
Content amount	1 ST
EAN	4024941318662
Length	96.5 mm
Width	94 mm
Height	200 mm
Weight	0.342 kg
Volume	1,814.2 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941826396
Length	325 mm
Width	217 mm
Height	210 mm
Weight	3.616 kg
Volume	13,588.4 ccm

