

## Wall mounting socket outlet low voltage - housing dimensions 126x83



Product description	
BALS-Prd.-Nr	4101
EAN	4024941041010
Product category	ELV wall mounting socket outlet
Current	63A
Number of poles	3p
Arrangement of phases	3P
Position of earth contact	6 h
Voltage	20 up to 25v

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	violet RAL 4005
Colour of appliance	Housing bottom grey RAL 7035, Housing top grey RAL 7035, Hinged lid violet RAL 4005
Connection design	with screw terminal
Maximum conductor size	16,0 qmm
Cable entry	1xM25 top, 2xM25 bottom
Height	158mm
Width	83mm
Depth	130mm
Dimension of enclosure	126x83 mm (HxW)
Material of enclosure	Polyamide
Contacts	the contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The cable entry is one at top open and two at bottom closed
	Lower part of housing rotatable by 180°
	4 cut out fixing holes in the lower part of housing

Logistics data	
Weight/pcs	0.405 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941041010
Length	130 mm
Width	83 mm
Height	158 mm
Weight	0.406 kg
Volume	1,704.82 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941946438
Length	330 mm
Width	216 mm
Height	260 mm
Weight	4.276 kg
Volume	17,062.5 ccm