

panel mounting socket outlet low voltage - flange 100x92,
fixing centers 85x77, angled execution



Product description	
BALS-Prd.-Nr	4202
EAN	4024941042024
Product category	ELV panel mounting socket Outlet, angled
Current	63A
Number of poles	3p
Arrangement of phases	3P
Position of earth contact	4 h
Voltage	20 up to 25 and 40 up to 50V

Product description	
Frequency	100 - 200Hz
Protection degree	IP44
Colour code	green RAL 6002
Colour of appliance	Hinged lid green RAL 6002, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	16,0 qmm
Cable entry	other
Height	100mm
Width	92mm
Depth	89mm
Flange size vertical in mm	100mm
Flange size horizontal in mm	92mm
Drill hole dist. vertical mm	85mm
Drill hole dist. horizontal mm	77mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	The inclination is 20°

Logistics data	
Weight/pcs	0.265 kg / Piece
Packaging	Bag
Content amount	1 ST
EAN	4024941042024
Length	89 mm
Width	92 mm
Height	100 mm
Weight	0.266 kg
Volume	818.8 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941935593
Length	258 mm
Width	183 mm
Height	212 mm
Weight	2.802 kg
Volume	8,750 ccm