

Panel mounting socket outlet low voltage - angled execution flange 68x62, fixing centers 53x47



| Product description | |
|---------------------------|--|
| BALS-Prd.-Nr | 4214 |
| EAN | 4024941042147 |
| Product category | ELV panel mounting socket Outlet, angled |
| Current | 32A |
| Number of poles | 2p |
| Arrangement of phases | 2P |
| Position of earth contact | 2 h |
| Voltage | 20 up to 25 and 40 up to 50V |

| Product description | |
|--------------------------------|--|
| Frequency | 300Hz |
| Protection degree | IP44 |
| Colour code | green RAL 6002 |
| Colour of appliance | Hinged lid green RAL 6002, Enclosure grey RAL 7035 |
| Connection design | with screw terminal |
| Maximum conductor size | 10,0 qmm |
| Cable entry | other |
| Height | 69mm |
| Width | 62mm |
| Depth | 70mm |
| Flange size vertical in mm | 68mm |
| Flange size horizontal in mm | 62mm |
| Drill hole dist. vertical mm | 53mm |
| Drill hole dist. horizontal mm | 47mm |
| Material of enclosure | Polyamide |
| Contacts | the contact carrier is made of polyamide, the contacts are brass nickel plated |

| Additional technical information | |
|----------------------------------|------------------------|
| | The inclination is 20° |

| Logistics data | |
|----------------|-----------------|
| Weight/pcs | 0.12 kg / Piece |
| Packaging | Bag |
| Content amount | 1 ST |
| EAN | 4024941042147 |
| Length | 71 mm |
| Width | 63 mm |
| Height | 70 mm |
| Weight | 0.121 kg |
| Volume | 313.11 ccm |
| Packaging | Carton |
| Content amount | 10 ST |
| EAN | 4024941836951 |
| Length | 207 mm |
| Width | 162 mm |
| Height | 142 mm |
| Weight | 1.3 kg |
| Volume | 3,750 ccm |



16 MB 12

| Ampere | 16 | 16 | 32 | 32 | | |
|----------------------------|------|------|------|------|--|--|
| Polzahl | 2 | 3 | 2 | 3 | | |
| a | 68,0 | 68,0 | 68,0 | 68,0 | | |
| b | 62,0 | 62,0 | 62,0 | 62,0 | | |
| c | 53,0 | 53,0 | 53,0 | 53,0 | | |
| d | 47,0 | 47,0 | 47,0 | 47,0 | | |
| e ø | 5,2 | 5,2 | 5,2 | 5,2 | | |
| f | 6,0 | 6,0 | 6,0 | 6,0 | | |
| h | 36,0 | 36,0 | 36,0 | 36,0 | | |
| i | 35,0 | 35,0 | 35,0 | 35,0 | | |
| α | 20° | 20° | 20° | 20° | | |
| l ø | 55,0 | 55,0 | 55,0 | 55,0 | | |
| Leiter mm ² min | 4 | 4 | 4 | 4 | | |
| Leiter mm ² max | 10 | 10 | 10 | 10 | | |