

panel mounting socket outlet low voltage - straight execution, flange 85x75, fixing centers 60x60



Product description	
BALS-Prd.-Nr	4302
EAN	4024941043021
Product category	ELV panel mounting socket outlet, straight
Current	63A
Number of poles	3p
Arrangement of phases	3P
Position of earth contact	12 h
Voltage	40 up to 50V

Product description	
Frequency	50/60Hz
Protection degree	IP44
Colour code	grey RAL 7035
Colour of appliance	Hinged lid grey RAL 7035, Enclosure grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	16,0 qmm
Cable entry	other
Height	90mm
Width	75mm
Depth	89mm
Flange size vertical in mm	85mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of polyamide, the contacts are brass nickel plated

Logistics data	
Weight/pcs	0.26 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941043021
Length	89 mm
Width	75 mm
Height	90 mm
Weight	0.261 kg
Volume	600.75 ccm