

## panel mounting socket outlet low voltage - straight execution, flange 55x55, fixing centers 45x45



| Product description       |  |
|---------------------------|--|
| BALS-Prd.-Nr              | 4319                                       |
| EAN                       | 4024941043199                              |
| Product category          | ELV panel mounting socket outlet, straight |
| Current                   | 32A  |
| Number of poles           | 3p   |
| Arrangement of phases     | 3P   |
| Position of earth contact | 4 h  |
| Voltage                   | 20 up to 25 and 40 up to 50V               |

| Product description            |  |
|--------------------------------|--|
| Frequency                      | 100 - 200Hz  |
| Protection degree              | IP44   |
| Colour code                    | green RAL 6002   |
| Colour of appliance            | Hinged lid green RAL 6002, Enclosure grey RAL 7035                             |
| Connection design              | with screw terminal  |
| Maximum conductor size         | 10,0 qmm   |
| Cable entry                    | other  |
| Height                         | 67mm   |
| Width                          | 55mm   |
| Depth                          | 59mm   |
| Flange size vertical in mm     | 55mm   |
| Flange size horizontal in mm   | 55mm   |
| Drill hole dist. vertical mm   | 45mm   |
| Drill hole dist. horizontal mm | 45mm   |
| Material of enclosure          | Polyamide  |
| Contacts                       | The contact carrier is made of polyamide, the contacts are brass nickel plated |

| Logistics data |                  |
|----------------|------------------|
| Weight/pcs     | 0.126 kg / Piece |
| Packaging      | Bag              |
| Content amount | 1 ST             |

| Logistics data |               |
|----------------|---------------|
| EAN            | 4024941043199 |
| Length         | 59 mm         |
| Width          | 55 mm         |
| Height         | 67 mm         |
| Weight         | 0.127 kg      |
| Volume         | 217.415 ccm   |
| Packaging      | Carton        |
| Content amount | 10 ST         |
| EAN            | 4024941969277 |
| Length         | 207 mm        |
| Width          | 162 mm        |
| Height         | 142 mm        |
| Weight         | 1.36 kg       |
| Volume         | 3,750 ccm     |



16 MB 13

| Ampere                     | 16   | 16   | 32   | 32   |  |  |
|----------------------------|------|------|------|------|--|--|
| Polzahl                    | 2    | 3    | 2    | 3    |  |  |
| a                          | 55,0 | 55,0 | 55,0 | 55,0 |  |  |
| b                          | 55,0 | 55,0 | 55,0 | 55,0 |  |  |
| c                          | 45,0 | 45,0 | 45,0 | 45,0 |  |  |
| d                          | 45,0 | 45,0 | 45,0 | 45,0 |  |  |
| e ø                        | 5,2  | 5,2  | 5,2  | 5,2  |  |  |
| f                          | 6,0  | 6,0  | 6,0  | 6,0  |  |  |
| h                          | 22,0 | 22,0 | 22,0 | 22,0 |  |  |
| i                          | 37,0 | 37,0 | 37,0 | 37,0 |  |  |
| k                          | 67,0 | 67,0 | 67,0 | 67,0 |  |  |
| l ø                        | 49,0 | 49,0 | 49,0 | 49,0 |  |  |
| m                          | 12,0 | 12,0 | 12,0 | 12,0 |  |  |
| Leiter mm <sup>2</sup> min | 4    | 4    | 4    | 4    |  |  |
| Leiter mm <sup>2</sup> max | 10   | 10   | 10   | 10   |  |  |