

plug low voltage - with cable gland, for cable diameter up to 24,5 mm



Product description	
BALS-Prd.-Nr	4402
EAN	4024941044028
Product category	ELV plug
Current	63A
Number of poles	3p
Arrangement of phases	3P
Position of earth contact	4 h
Voltage	20 up to 25 and 40 up to 50V

Product description	
Frequency	100 - 200Hz
Protection degree	IP44
Colour code	green RAL 6002
Colour of appliance	Enclosure green RAL 6002, Cable gland grey RAL 7035
Connection design	with screw terminal
Maximum conductor size	16,0 qmm
Cable entry	with cable gland
Height	173mm
Width	66mm
Depth	78mm
Material of enclosure	Polyamide
Contacts	The contact carrier is made of high temperature resistant material, the contacts are brass nickel plated

Additional technical information	
	With cable gland, For cable diameter up to max. 24,5 mm

Logistics data	
Weight/pcs	0.24 kg / Piece
Packaging	Bag
Content amount	1 ST

Logistics data	
EAN	4024941044028
Length	78 mm
Width	66 mm
Height	173 mm
Weight	0.241 kg
Volume	890.604 ccm
Packaging	Carton
Content amount	10 ST
EAN	4024941819428
Length	275 mm
Width	175 mm
Height	137 mm
Weight	2.525 kg
Volume	5,737.5 ccm