

Domestic panel mounting socket outlet with increased contact protection (shutter) for stationary distributor systems - flange 75x75 fixing centers 60x60



Product description	
BALS-Prd.-Nr	7110809
EAN	4024941854108
Product category	Domestic panel mounting socket outlet QUICK-CONNECT screwless push-contact System F German standard
Current	16A
Number of poles	3p
Arrangement of phases	2P+PE
Voltage	250V~

Product description	
Frequency	AC
Protection degree	IP54
Colour code	blue RAL 5015
Colour of appliance	Enclosure blue RAL 5015, Hinged lid blue RAL 5015
Connection design	screwless
Maximum conductor size	2,5 qmm
Height	75mm
Width	75mm
Depth	47.5mm
Flange size vertical in mm	75mm
Flange size horizontal in mm	75mm
Drill hole dist. vertical mm	60mm
Drill hole dist. horizontal mm	60mm
Material of enclosure	plastic
Contacts	the contact carrier is made of polyamide, the contacts are brass nickel plated

Additional technical information	
	The connection is rear, For use in stationary distributor distributor systems, With increased contact protection (shutter)

Logistics data	
Weight/pcs	0.093 kg / Piece

Logistics data	
Packaging	Bag
Content amount	1 ST
EAN	4024941854108
Length	47.5 mm
Width	75 mm
Height	75 mm
Weight	0.094 kg
Volume	267.188 ccm
Packaging	Carton
Content amount	20 ST
EAN	4024941323499
Length	275 mm
Width	175 mm
Height	137 mm
Weight	1.985 kg
Volume	5,737.5 ccm



18 MB 107